CSL Series



Scan for PDF

CSL Series

FEATURES

- Variable GVWR up to 18,800 lbs
- Variable Payload up to 15,000 lbs
- Multiple Axle Capacities
- 2" Oak Flooring Anchored on Each End with Carriage Bolts
- ICC & DOT Approved LED Lights
- Spring Assisted Ramps
- 24" Deavertail
- 81" Between Fenders (Deck Width Decreases As Axle Size Increases)
- Variable Deck Lengths

 GVWR Range	14,000 - 18,800 lbs
Payload Range	11,000 - 15,000 lbs
Axle Manufacturer	Dexter
 Axle Size	7,000 - 12,000 lbs
Tires	235/80R16 , 215/75R17.5 , 235 / 75R17.5
 Wheels	16" x 6", 17.5" x 6"
 Brakes	Electric or Hydraulic
 Overall Width	102"
 Overall Lengths	23' - 29'
 Jack	12,000 lb Drop Leg
 Deck Lengths	16' - 22'
 Deck Height	23"
 Hitch	Lunette Eye or Ball Coupler
 Width Between Fenders	81"

OPTIONS

- Gooseneck Upgrade
- Pallet Fork Carrier with Ratchet Strap
- Spare Tire and Wheel
- Wood Inlaid Ramps
- Back Up Lights
- Tool Box

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

