PTB - 81, 111, 141







O Scan for PDF

866.462.7665 TO SPEAK WITH A REPRESENTATIVE

PTB- 81, 111, 141

FEATURES

- Variable GVWR up to 26,000 lbs
- Variable Payload up to 22,400 lbs
- Variable Length Adjustments
- Cargo Bed Between Center and Rear Bolsters
- Tubular Construction
- 6 Position Adjustable Hitch
- Multiple Axle Capacities
- Extendable Tongue with Greasable Steel Roller and Nylon Wear Pads
- Internally Wired Air and / or Electrical Lines (No Coil Cords)
- Multiple Stanchion Configurations
- Single Axle, Dual Wheels
- 4" W x 15' Pole Straps and Winch Binders Located at Each Bolster

0	b.	TΙ	0	N	S
---	----	----	---	---	---

- Optional 60" and 89" Front Bolster Upgrade
- · Galvanized Finish Upgrade
- Optional Pole Mounted Light bar
- Optional Tool Box (Aluminum Tread Plate)
- Bedliner in Cargo Floor

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SPECIFICATIONS

11,700 - 26,000 lbs		
8,200 - 22,400 lbs		
Dexter		
10,000 - 20,000 lbs		
235/80R16, 215/75R17.5, 255/70R22.5		
16" x 6" , 17.5" x 6.75" , 22.5 Duals		
95"		
Fixed 12,000 lb Drop Leg		
8' - 14' Long		
18" T x 18" D x 24" - 48" L		
20' - 28'		
30' - 43'		
95"		
45" , 60" , and 95"		
2 1/2" or 3" Lunette Eye		
42"		

PTB - 81



PTB - 111



PTB- 141



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

