RT SxS Series



Scan for PDF

RT SxS Series

FEATURES

- Variable GVWR up to 23,500
- Variable Payload up to 18,500
- Capacity up to 6 Reels in a Side by Side Configuration
- Capable of Carrying up to (6) 72" D x 40" W Reels
- Heavy Duty Slam Lock Reel Bar Retainers
- Variable Length
- Custom Reel Configurations
- Cargo Bed
- Contoured A-Frame Tool Box
- ICC & DOT Approved LED Lights

· · · · · · · · · · · · · · · · · · ·	GVWR Range	16,000 - 23,500 lbs
	Payload Range	12,000 - 18,500 lbs
	Axle Manufacturer	Dexter
	Axle Size	7,000 - 10,000 lbs
	Tires	235/80R16, 215/75R17.5
	Wheels	16" x 6" , 17.5" x 6.75"
	Maximum Reel Diameter	Up to 72"
	Maximum Reel Width	Up to 40"
	Reel Bar	2 7/8" OD
	Overall Width	101"
	Reel Rack Brake Sizes	10", 16", or 20"
	Cable Gathering Windows	UHMW High Strength Plastic
	Jack	Fixed 12,000 lb Drop leg
	Overall Length Range	12' - 35'
	Tool Box	14" H x 13" D x 78" L Contoured to A-frame

OPTIONS

- 10" 20" Overspin / Tensioning Brakes Upgrade
- Self Contained Hydraulic Power Pack
- Galvanized Finish Upgrade
- Hydraulic Takeup/ Payout Upgrade
- Individual Cable Gathering Windows

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

