













Reel Stands

FEATURES

- Variable Reel Diameters
- Variable Reel Widths
- Multiple Reel Weight Capacities
- Tubular Steel Construction
- Steel Tube Cross Supports that Double as Fork Pockets
- Flat or Skid Mounted Base
- Multiple Reel Brake Sizes
- Single or Multiple Reel Configurations
- Custom Design Per Application

U	\sim
Z	
	_
<u>'</u>	I
	_
7	
D	
U	2

Overall Width Range	76.5" - 81.5" (Pending Reel Size)
Overall Length Range	63" - 107" (Pending Reel Size)
Reel Weight	Up To 30,000 lbs
Reel Width	96" Max (Designed to Customer Specs.)
Reel Diameter	156" Max (Designed to Customer Specs.)
Reel Bar	2 7/8" OD - 5" OD (Designed to Reel Center Hole)
Reel Brake	10" - 20"
Paint	Two-Part Acrylic Polyurethane
Take Up Line Pull	Up to 3,000 lbs (Per Reel Size Configuration)
Take Up Pressure	2,700 PSI Continuous

OPTIONS

- 10"-20" Overspin / Tensioning Brakes Packages
- Hydraulic Take Up / Pay Out Assembly with High Torque Drive
- Self Contained Hydraulic Power Pack Unit (Gas or Diesel)
- Truck Bed Option
- V Grove Tensioner Attachment
- Expandable Configuration Option

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.







For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

