

SINGLE DRUM PULLER/TENSIONER







SDPT-3500

FEATURES

- 3,500 lbs at Rated Pulling Capacity (Quality Tested at 500 lbs Above Rated Capacity)
- Fully Hydrostatic Drive Pump Capable of 34 gpm.
- Level Wind is Hydraulically Actuated with Variable Speed Control
- All Unit Operator Controls are Located at the Operator's Station
- Drum Engagement Actuated at Panel
- Full Operator's Instruction Manual
- Spring Applied Hydraulic Pressure Released Safety Brake
- Drum Equipped with its own Direct Drive Hydraulic Motor Gearbox Assembly (No Chain and Sprocket)
- Full-Width Drum Tarp for Protection of Rope
- Operator's Seat Safety Screen
- Access Step, Located on Both Sides of A-frame
- 16 in. Overspin Payout Brake (Aluminum Bronze)
- Includes In Service Training: Classroom and in Field Demos
- Overhead Canopy

OPTIONS

- Hydraulic Actuated Pay-Out Brake in Lieu of Manual
- Galvanized Finish
- Reconductoring Reel
- · Auxiliary P-Line Drive
- Overhead/Underground Combo-Pull Out Fairled Assembly, Steel Wire Rope

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

Rated Line Pull	3,500 lbs
Max Line Speed	2-3 mph Average
Standard Rope	5/8 in. Diameter Sampson Tenex
Standard Rope Length	6,000 ft
Drum	Single Drum Configuration
Engine Make	Yanmar Tier 4 Final Diesel
Engine HP	47.6 hp @ 3000 rpms
Fuel Capacity	18 gal
A-Frame	5'
Overall Length	15' 2"
Max Width	100"
Overall Weight	Approx. 6,500 lbs
GVWR	11,700 lbs
Axle Type	Single Torflex Axle
Axle Capacity	10,000 lbs per Axle
Brakes	Electric on all Wheels
Tires	(2) 235 / 75R17.5 LR-H
Wheels	(2) 6.75" x 17.5" Single Wheels
	(8-hole on 6'-1/2" bolt circle)
Mud Flaps	(1) Pair Mud Flaps
Front Jack	Heavy Duty Hydraulic
Rear Jacks	(2) Hydraulic Stabilizer Jacks

UNDERGROUND PULL OUT



P-LINE DRIVE UPGRADE



SPECIFICATIONS

GALVANIZED FINISH



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

