# **SL Series**







K WITH A REPRESENTATIVE ine at brooksbrotherstrailers.com

Scan for PDF

## **SL Series**

## **FEATURES**

- Variable GVWR up to 18,800 lbs
- Variable Payload up to 14,500 lbs
- Multiple Axle Capacities
- 2" Oak Flooring
- Board Ends Anchored on Each End with Carriage Bolts
- ICC & DOT Approved LED Lights
- Spring Assisted Ramps
- Angular Main Frame with Channel Cross Members
- 5" Tall Sides
- Tubular Tongue

0	<b>P</b> 1	Ш	n	N	
v	ГΙ	יוו	u	IV	_

- Gooseneck Upgrade
- Pallet Fork Carrier with Ratchet Strap
- · Spare Tire and Wheel
- · Wood Inlaid Ramps
- · Back Up Lights
- Tool Box
- · Additional D-Rings

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

# SPECIFICATIONS

GVWR Range	14,000 - 18,800 lbs		
Payload Range	11,000 - 14,500 lbs		
Axle Manufacturer	Dexter		
Axle Size	6,000 - 8,000 lbs		
Tires	235/80R16, 215/75R17.5		
Wheels	16" x 6", 17.5" x 6.75"		
Brakes	Electric		
Overall Width	102"		
Overall Lengths	23' - 27'		
Jack	12,000 lb Drop leg		
Deck Lengths	16' - 22'		
Deck Height	16"		
Hitch	Lunette Eye or Ball Coupler		
Width Between Fenders	81"		

## CUSTOM OPTIONS



## STANDARD UNIT



## **UPGRADED AXLE CONFIGURATIONS**



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

