SRT Series







Scan for PDF

SRT Series

FEATURES

- Steel Tube Main Frame Construction
- 6-Position Adjustable Hitch
- Heavy Duty Slam Lock Reel Bar Retainers
- 1/8" Steel Diamond Tread Plate Fenders
- Torflex Axles
- 2 7/8" Reel Bar with Locking Collar
- ICC & DOT Approved LED Lights
- 2 Part Polyurethane Paint

71111111	ww
U	\neg
Z	_
	~
_	_
	21112
	`
_	_
(11111) 11	3111
1111	_
-	_
300000	
	т
<	ζ
· 5	Ĺ
ζ	こり
(ر
(ر
7	۷
7	۷
(۷
7	۷
JEIL	ر =
JEIL	ر =
7	ر =
CIEIC	2 = 5
CIEIC	2 = 5
JEIL	2 = 5
FUEIL	ノニンゴ
FUEIL	ノニンゴ
DECIEIC	ノニンユー
DECIEIC	ノニンユー
FUEIL	ノニンユー
DECIEIC	ノニンユー
DECIEIC	ノニンユー
DECIEIC	ノニンユー

GVWR Range	8,200 - 18,800 lbs
Payload Range	5,200 - 14,800 lbs
Axle Manufacturer	Dexter
Axle Size	7,000- Tandem 8,000 lbs
Tires	235/80R16, 215/75R17.5
Wheels	16" x 6", 17.5 x 6.75
Overall Width	98"
Overall Length	134'
Jack	10,000 lb Drop Leg
Reel Capabilities	10' Diameter x 60" Wide (with custom offerings available)
Hitch	Adjustable 2 1/2" or 3" Lunette Eye

OPTIONS

- Increased Axle Sizes or Tandem Axle Upgrade
- Custom Reel Configurations
- Galvanized Finish
- Self Contained Power Pack
- 10"-20" Overspin/Tensioning Brake Upgrades
- Hydraulic Take up/Payout Assemblies

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

CUSTOM REEL CONFIGURATION



GALVANIZED FINISH



TANDEM AXLE CONFIGURATION



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

