TRT S x S



🛃 Scan for PDF

TRT S x S

FEATURES

- Full 360 Degree Rotation Lockable Every 15 Degrees
- Deck Equipped with 1/8" Steel Diamond Tread Plate
- Steel Tube Main Frame Construction
- Vertical Reinforcement Rack Supports
- 1/8" Steel Diamond Tread Plate Fenders
- 6-Position Adjustable Hitch
- Heavy Duty Split Reel Rack Assembly with Self Lubricating Bronze Bushings
- Dual Rear Stabilizer Jacks
- ICC & DOT Approved LED Lights
- Heavy Duty Slew Bearing Rated at 106,798 lbs Axial and 40,000 ft-lbs Moment Load Capacity

SPECIFICATIONS		
	GVWR Range	8,200 - 23,500 lbs
	Payload Range	5,000 - 18,500 lbs
	Axle Manufacturer	Dexter
	Axle Size	6,000 - 10,000 lbs
	Tires	235/80R16 , 215/75R17.5 , 235/75R17.5
	Wheels	16" x 6" , 17.5" x 6.75"
	Maximum Reel Diameter	60"
	Maximum Reel Width	40"
	Reel Bar	2 7/8" DOM
	Overall Width	101"
	Jack	Fixed 12,000 lb Drop Leg
	Hitch	2 1/2" Lunette Eye
		1

OPTIONS

- Available in Single, Dual and Triple Turret Design for 2-6 Reel Capacity
- Self Contained 14HP Gas or 19HP Diesel Engines
- Hydraulic Take-up / Payout Assemblies
- 10"-20" Overspin / Tensioning Brake Upgrade
- Galvanized Finish
- Anti Skid Surfacing

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SINGLE TURRET SIDE BY SIDE



DUAL TURRET SIDE BY SIDE WITH TAKE UP AND OVERSPIN BRAKES



TRIPLE TURRET SIDE BY SIDE WITH OVERSPIN BRAKES



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

