UP 8000-10000





UNDERGROUND PULLER



Scan for PDF

UP 8000-10000

FEATURES

- 8,000-10,000 lbs at Rated Pulling Capacity (Quality Tested at 500 lbs Above Rated Capacity)
- 2,500' of 3/8" (8,000 lb Puller) or 2,200' of 7/16" (10,000 lb Puller) HD
 3-Strand Rotation Resistant Steel Cable
- Level Wind With Reversing Lead Screw Design
- Elevated Operator Station or Stand-Beside Ground Controls
- Hydraulicly Actuated Self Supported 3-Axis Boom (Up, Down, Left, Right, Retract, and Extend)
- Hydrostatic Controlled Pay-in and Pay-out (No Gear Box or Transmission)
- 35.5 HP Yanmar Tier 4 Final Diesel Engine (8,000 lb Puller) or 47.6 HP Yanmar Tier 4 Final Diesel Engine (10,000 lb Puller)
- Hydraulically Driven Twin Capstain Bullwheels Heat Treated for Longer Durability
- New and Easy to Use Dynamometer That Measures Distance, and Line Tension
- Dynamometer Equipped with USB Output to Record Live Pulling Data
- Compact Design
- Operator Controls Located at Operators Station
- (2) Grounding Lugs
- (3) Hydraulic Jacks Standard W/ Jack Stabilizer Pads and Storage on Trailer
- Tool Box

OPTIONS

- 210 CFM Self Contained Air Compressor Upgrade (Compressor Controls Now Located at Operator Station)
- Galvanized Finish Upgrade
- Color: White, Red, Black, Safety Yellow
- Air Adapter Kit and Underground Roller Upgrade
- Manhole Jib Option
- Wireless Remote With Live Line Pull Readout Option
- 49 HP Electric Engine Option

Additional accessories available through Brooks Brothers Trailers & Equipment including pulling grips, swivels, pilot line systems, and running grounds.

SPECIFICATIONS

GVWR	9,400 lbs (No Air) , 14,000 lbs (With Air)
Overall Weight	7,600 lbs (No Air) , 10,500 lbs (With Air)
Overall Frame Length	173"
Overall Width	90"
Pulling Capacity	8,000 and 10,000 lbs
Cable Size	3/8" x 2,500' (8,000 lb) or 7/16" x 2,200' (10,000 lb)
Cable Type	HD 3-Strand Rotation Resistant
Levelwind	Mechanical Reversing Screw
Self Supported Boom	Hydraulically Controlled
Boom Movement	Left, Right, Up, Down
Boom Extension Length	20"
Engine	35.5 HP Yanmar Tier 4 Final Diesel (8,000 lb Puller) or 47.6 HP Yanmar Tier 4 Final Diesel (10,000 lb Puller)
Dynamometer	Rugged Controls RL-05
Display	Rugged Controls RPC-80X
Bullwheels	Heat Treated Twin 10" OD
Air Compressor Manufacture	VanAir - Utility Mount
Air Compressor Specifications	210CFM at 100PSI
Air Compressor Power Train	74 HP John Deere Diesel
Air Hose	Retractable Reel With 50' Hose
Roller Construction	Nylatron

STAND-BESIDE CONTROLS WITH AIR



AIR UPGRADE WITH GALVANIZED FINISH



49 HP ELECTRIC ENGINE OPTION



For more complete information on Brooks Brothers Trailers products and services, visit us on the web at www.brooksbrotherstrailers.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact a Brooks Brothers Trailers representative for all available options. Brooks Brothers Trailers and the Brooks Brothers Trailers logo are trademarks of Brooks Brothers Trailers in the United States and various other countries and may not be used without permission. Brooks Brothers Trailers and Equipment. All Rights Reserved.

